



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
 A-A-3058
 FIRE RETARDANT COATING
 PAGE 1 OF 2

PRODUCT: A-A-3058

DESCRIPTION: An elastomeric, waterbased fire resistant coating that is formulated with a blend of acrylic resins. This primer has excellent flexibility for expansion and contraction resistance. It can be used over hairline cracks and has a Class B fire test rating over various surfaces with combustible substrates and a Class A fire testing rating for steel and other surfaces with a non-combustible substrate.

PROPERTIES:

COLORS.....	Full	Range
SOLIDS(Weight).....	71	- 74%
SOLIDS(Volume).....	53	- 56%
THEORETICAL COVERAGE.....	150	sq.ft/gal
ELONGATION.....	325 -	350%

DRYING	TIME-AT	75	DEGREES	F:	TO
TOUCH.....	4	Hours	TO		
RECOAT.....				Overnight	
VEHICLE	TYPE.....		Elastomeric/Acrylic		
WEIGHT/GAL.....	12.2 to	12.4	lbs/gal		

ADVANTAGES:

- (1). Low Volatile Organic Compound Content
- (2). Excellent Exterior Durability
- (3). Excellent Flexibility
- (4). Extremely Weather Resistant
- (5). Water Reducible
- (6). Meets A-A-5048 Specification

USES:

- (1). Asphalt
- (2). Aluminum
- (3). Concrete
- (4). Polyurethane Roofs
- (5). Wood
- (6). Galvanized Steel



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
A-A-3058
FIRE RETARDANT COATING
PAGE 1 OF 2

APPLICATION & REDUCTION:

TriCom's Waterbase Fire Retardant Primer is ready for use at packaged consistency. For brushing and rolling, use at packaged consistency.

For spraying, thin only as needed for proper atomization. Thinning is not normally recommended.

SURFACE PREPARATION:

Surface must be clean, dry and free of all contamination before application. Cracks and imperfections must be patched, mildew removed, loose or peeling paint removed by sanding or scraping.

STEEL:

Surface must be clean and free of all oil, grease and foreign material. Badly rusted or pitted steel should be cleaned by commercial sandblasting.

PRECAUTIONS:

KEEP OUT OF THE REACH OF CHILDREN!

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.

KEEP FROM FREEZING!