



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET

A-A-50574

S/G ALKYD ENAMEL

PAGE 1 of 2

PRODUCT: A high quality, odorless, semi-gloss alkyd enamel for use on all interior wood, metal, or masonry surfaces. This product is extremely durable with excellent flow and leveling characteristics.

Description: A specially formulated semi-gloss, odorless, alkyd enamel for interior wood, metal, and masonry surfaces. A-A-50574 semi-gloss alkyd enamels are durable, washable, and easy to apply. It has excellent hiding power, and scrubbing properties.

PROPERTIES: COLORS..... Fed Std. 595B
MAX VOLATILE ORGANIC COMPOUNDS (VOC's)..... 250 G/L
SOLIDS (Volume)..... 61-63%
GRIND..... 6 Minimum
DRYING TIMES (75°F):
TO HANDLE..... 2-4 Hours
DRY HARD..... Within 12 Hours
Gloss (60 Degree)..... 45-70%
WEIGHT/GALLON..... 10.2 - 10.6 Lbs/Gal

ADVANTAGES: (1). Meets A-A-50574
(2). Excellent Hide
(3). Extremely Durable
(4). Excellent Flow and Leveling
(5). Low Odor for Interior Use
(6). Extremely Washable

USES: (1). Wood
(2). Metal
(3). Cabinets
(4). Masonry
(5). Furniture



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET

A-A-50574

S/G ALKYD ENAMEL

PAGE 2 of 2

APPLICATION & REDUCTION:

A-A-50574 semi-gloss, odorless alkyd Enamels are formulated for brush, roll, or spray applications. For spraying, thin up to 10% or as needed with odorless mineral spirits. For brushing, use at packaged consistency or thin as needed with odorless mineral spirits.

SURFACE PREPARATION:

Surface must be clean, dry, free of all contamination, and properly prepared before application.

PRECAUTIONS:

Contents are FLAMMABLE.
Keep away from heat and open flame.
KEEP OUT OF THE REACH OF CHILDREN.
Do not take internally.
Avoid breathing vapor or mist.
Do not use in tank or pit without proper protection.
Read Material Safety Data Sheet before use of this product.