



# TECHNICAL DATA SHEET

**TECHNICAL DATA SHEET  
WALKWAY COMPOUND-NONSLIP  
A-A-59166**

**PRODUCT:** A non-slip walkway coating for the exterior of aircraft surfaces.

**DESCRIPTION:** A-A-59166 WALKWAY COATING is a nonslip walkway compound coating for use on walkways of exterior aircraft surfaces. Type I is smooth and can be applied by brushing or rolling, as well as spraying. Type II contains grit for additional non-skid properties and is for brushing and rolling application only.

**PROPERTIES:**

COLORS..... Per Fed.Std. 595B  
TYPE I: Smooth Texture  
TYPE II: Grit Added  
FINISH..... Lusterless  
SOLIDS(Weight)..... 52 - 65%

**DRYING TIMES:**

TACK FREE..... 15 Minutes  
RECOAT..... 30 Minutes  
DRY THROUGH..... 6 Hours  
FULL HARDNESS..... 24 Hours  
Full Cure.....7 days

- ADVANTAGES:**
- (1). Non-Slip.
  - (2). Air Dry.
  - (3). Brushable.
  - (4). Durable.
  - (5). Fast Dry.

- USES:**
- (1). Exterior Aircraft Walkways.
  - (2). Heavy Traffic Areas.
  - (3). Non-Slip Requirements.

**APPLICATION:** Apply by brush or roll methods (or spray for Type I). Thin with MIL-T-81772B Type III Reducer or TT-X-916 Xylene as needed to facilitate proper flow. For Type II, Do not over brush so that an even distribution of the grit is achieved.