



# TECHNICAL DATA SHEET

TECHNICAL DATA SHEET  
ASTM D3955-13  
Grade DA

- PRODUCT:** An air dry, moisture and fungus resistant clear gloss varnish. Protects and insulates.
- DESCRIPTION:** ASTM D3955-13 type coating is a moisture and fungus resistant varnish for the treatment of communications, electronic and related equipment. May also be used on tools and materials that are to be transported by ship. Dries to a smooth, hard film that resists cracking and splintering.
- PROPERTIES:**
- |                     |          |
|---------------------|----------|
| COLOR.....          | Clear    |
| FINISH.....         | Gloss    |
| SOLIDS(Weight)..... | 51 - 54% |
- DRYING TIMES:**
- |                   |                       |
|-------------------|-----------------------|
| SET-TO-TOUCH..... | Within 60 Minutes DRY |
| TACK FREE.....    | Within 5 Hours        |
- ADVANTAGES:**
- (1). Fast Dry
  - (2). Moisture Resistant
  - (3). Fungus Resistant
  - (4). Air Dry
- USES:**
- (1). Electronic Equipment
  - (2). Communications Equipment
  - (3). Electrical Equipment
  - (4). Tools
  - (5). Electric Parts/Wires
- APPLICATION:** Surface must be clean, dry and properly prepared before application. May be applied by brush, roll, dip, or spray.
- AEROSOL CANS:** Vigorously shake can for one minute to to thoroughly mix coating. Shake can occasionally while spraying. Hold can approximately 12" from surface to be painted.



# TECHNICAL DATA SHEET

---

SHELF LIFE: 1 YEAR FROM DATE OF MANUFACTURE \*\*  
READ MSDS BEFORE USE \*\*