



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
CERAMIC COATING
PAGE 1 OF 2

PRODUCT: A water-base, elastomeric coating fortified with ceramic beads for superior durability, flexibility, heat and weather resistance.

DESCRIPTION: An elastomeric coating formulated with a blend of acrylic elastomeric resins to provide excellent exterior durability. This coating can be used as a system for roofs along with fiberglass membranes and cloth. It has excellent flexibility for expansion and contraction resistance. Can be used over hairline cracks. Fortified with ceramic beads for increased protection against heat and sun damage.

PROPERTIES: COLORS.....Full Range
SOLIDS(Weight).....71 - 74%
SOLIDS(Volume).....53 - 56%
THEORETICAL COVERAGE.....100 sq.ft/gal
ELONGATION.....325 - 350%
DRYING TIME-AT 75 DEGREES F:
TO TOUCH.....4 Hours
TO RECOAT.....Overnight
VEHICLE TYPE.....Elastomeric/Acrylic
WEIGHT/GAL..... 12.2 to 12.4 lbs/gal

ADVANTAGES: (1). Low Volatile Organic Compound Content
(2). Excellent Exterior Durability
(3). Excellent Flexibility
(4). Extremely Weather Resistant
(5). Water Reducible
(6). Ceramic Fortified.

USES: (1). Asphalt
(2). Aluminum
(3). Concrete
(4). Polyurethane Roofs
(5). Wood Roofs
(7). Walls
(8). Galvanized Steel
(9). Stucco



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
CERAMIC COATING
PAGE 2 OF 2

APPLICATION & REDUCTION:

Intrepid's Ceramic Coating is ready for use at packaged consistency. For brushing and rolling, use at packaged consistency.

For spraying, thin only as needed for proper atomization. Thinning is not normally recommended.

SURFACE PREPARATION:

Surface must be clean, dry and free of all contamination before application. Cracks and imperfections must be patched, mildew removed, loose or peeling paint removed by sanding or scraping.

STEEL:

Surface must be clean and free of all oil, grease and foreign material. Badly rusted or pitted steel should be cleaned by commercial sandblasting and primed the same day.

PRECAUTIONS:

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.