



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
MIL-D-5549B CLEAR GLOSS DOPE
PAGE 1 OF 2

PRODUCT: An exterior dope lacquer coating that meets MIL-DTL-5549B for protection of metal surfaces.

DESCRIPTION: A general purpose, exterior protective dope lacquer coating for metal surfaces.

PROPERTIES: COLORS..... All 595 Colors MAX
VOC..... 340 G/L
DRY HARD..... Within 40 Minutes

RESISTANT TO:

HEAT
WEATHER
WATER
HYDROCARBONS
LUBRICATING OIL

ADVANTAGES: (1). MIL-DTL-5549B
(2). Weather Resistant
(3). Fast Dry
(4). Durable Exterior Coating

USES: (1). Steel
(2). Machinery
(3). Aircraft
(4). Vehicles
(5). Equipment
(6). Towers



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
MIL-D-5549B CLEAR GLOSS DOPE
PAGE 2 OF 2

APPLICATION & REDUCTION:

MIL-DTL-5549B dope Lacquers can be applied by conventional or airless spray application. For spraying, thin up to 10% or as needed with MIL-T-81772B TY.3 Thinner. For brushing, reduce up to 10% with MIL-T-81772B TY.3 Thinner Brush small areas only.

SURFACE PREPARATION:

Surface must be clean, dry and free of all contamination before application of primer.

STEEL:

Surface must be clean and free of all oil, grease and foreign material. Badly rusted or pitted steel should be cleaned by commercial sandblasting and primed the same day.

PRECAUTIONS:

Contents are FLAMMABLE.

Keep away from heat and open flame.

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.