



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
MIL-DTL-700B Form. 20L
INTERIOR DECK ENAMEL
PAGE 1 OF 2

PRODUCT: A general purpose, low VOC (<340 G/L) enamel with good durability for use on decking, steel furniture, machinery and equipment aboard ships or at naval installations. Available in two classes and three types as listed below.

PROPERTIES:

COLORS..... Gray
SOLIDS CONTENT (WEIGHT)..... 26-39%
GRIND..... Not Under 6
SPECULAR GLOSS..... 25 - 50
VISCOSITY..... 70 - 95 KU
VOC..... <340 G/L

DRYING TIME-AT 75 DEGREES F:

SET-TO-TOUCH: 2 HR
DRY HARD: 7 HOURS

USES:

- (1). Decking
- (2). Steel
- (3). Machinery
- (4). Furniture
- (5). Equipment



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
MIL-DTL-700B Form. 20L
INTERIOR DECK ENAMEL
PAGE 2 OF 2

APPLICATION & REDUCTION:

MIL-DTL-700B Form. 20L Enamel can be applied by brush or spray. This material should be thinned 15 - 20% with Xylene or MIL-T-81772B Ty. III thinner. Spray one tack coat followed by one full wet coat.

SURFACE PREPARATION:

Surface must be clean, dry and free of all contamination before application of primer.

STEEL:

Surface must be clean and free of all oil, grease and foreign material. Badly rusted or pitted steel should be cleaned by commercial sandblasting and primed the same day.

PRECAUTIONS:

Contents are FLAMMABLE.

Keep away from heat and open flame.

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.