



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
MIL-V-13750B
PERMANENT RESIN COATING
PAGE 1 of 2

PRODUCT DESCRIPTION:

A clear or aluminum pigmented phenolic (air dry) varnish for use on ammunition. Class A is Tung oil based, and Class B is Linseed oil based. It is formulated as a low VOC coating, so it meets composition G (general use) and Composition L (low VOC) requirements for VOC's.

TYPICAL PROPERTIES:

Ty. I

COLOR..... Clear
RESIN SOLIDS(Weight)..... 25%
DRYING TIMES:
SET TO TOUCH..... 30 Minutes
DRY THROUGH..... 60 Minutes

Ty. II

COLOR..... Clear
RESIN SOLIDS(Weight)..... 12.5%
DRYING TIMES:
SET TO TOUCH..... 10 Minutes
DRY THROUGH..... 60 Minutes

Ty. III

COLOR..... Aluminum
RESIN SOLIDS(Weight)..... 25%
DRYING TIMES:
SET TO TOUCH..... 30 Minutes
DRY THROUGH..... 90 Minutes



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
MIL-V-13750B
PERMANENT RESIN COATING
PAGE 1 of 2

Ty. IV

COLOR..... Aluminum
RESIN SOLIDS(Weight)..... 12.5%
DRYING TIMES:
SET TO TOUCH..... 10 Minutes
DRY THROUGH..... 20 Minutes

- ADVANTAGES:**
- (1). Fast Dry
 - (2). Moisture Resistant
 - (3). Fungus Resistant
 - (4). Air Dry

- USES:**
- (1). Electronic Equipment
 - (2). Communications Equipment
 - (3). Electrical Equipment
 - (4). Ammunition
 - (5). Electric Parts/Wires

APPLICATION: Surface must be clean, dry and properly prepared before application. May be applied by brush, roll, dip, or spray.

AEROSOL CANS: Vigorously shake can for one minute to thoroughly mix coating. Shake can occasionally while spraying. Hold can approximately 12" from surface to be painted.

SHELF LIFE: 1 YEAR FROM DATE OF MANUFACTURE **
READ MSDS BEFORE USE **

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN.
USE WITH ADEQUATE VENTILATION.
AVOID CONTACT WITH SKIN AND EYES.
READ MATERIAL SAFETY DATA SHEET BEFORE USING.
CONTENTS ARE FLAMMABLE.