



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
WALKWAY COMPOUND
NONSLIP MIL-W-5044C

PRODUCT: A non-slip walkway coating with non-skid properties.

DESCRIPTION: **MIL-W-5044C WALKWAY COATING** is a single component nonslip walkway compound coating for use on walkways of exterior aircraft surfaces. Type II contains grit for added non-skid properties and is for brushing and rolling applications only.

PROPERTIES:

COLORS..... Per Fed.Std. 595B
TYPE I: Smooth - No Grit
TYPE II: Grit Added
FINISH..... Flat or Semigloss
Solids(Weight)..... 52 - 55%
DRYING TIMES:
TACK FREE..... 15 Minutes
RECOAT..... 30 Minutes
FULL HARDNESS..... 24 Hours

ADVANTAGES:

- (1). Non-Slip.
- (2). Air Dry.
- (3). Fast Dry.
- (4). Durable.

USES:

- (1). Exterior Aircraft Walkways.
- (2). Heavy Traffic Areas.
- (3). Non-Slip Requirements.

APPLICATION: Apply by brush or roll methods. Thin with MIL-T-81772B Type III Reducer or TT-X-916 Xylene as needed to facilitate proper flow. Do not over brush Type II so that an even distribution of the grit is achieved.