



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
P-D-680B

PRODUCT DESCRIPTION:

Dry cleaning and degreasing solvent consisting of three types of petroleum distillates: Ty. I - "Stoddard Solvents", Ty. II - 140° Fahrenheit Solvent, and Ty. III - 200° Fahrenheit Solvent (unavailable through TriCom Coatings, Inc.) They are used for dry cleaning, spot and stain removing, and for degreasing of machine parts in equipment maintenance.

TYPICAL PROPERTIES:

- (1). **FLASH POINT**
Ty. I - 100° Fahrenheit
Ty. II - 140° Fahrenheit
Ty. III - Not Available through TriCom Coatings, Inc.
- (2). **INITIAL BOILING POINT**
Ty. I - 149° Fahrenheit
Ty. II - 177° Fahrenheit
Ty. III - Not Available through TriCom Coatings, Inc.
- (3). **WEIGHT PER GALLON**..... 6.44 - 6.6 Lbs
- (4). **PERCENT VOLATILES**..... 100%

PRECAUTIONS:

USE WITH ADEQUATE VENTILATION.
AVOID CONTACT WITH SKIN AND EYES.
READ MATERIAL SAFETY DATA SHEET BEFORE USING.
KEEP OUT OF THE REACH OF CHILDREN.
FOR INDUSTRIAL USE ONLY.
CONTENTS ARE FLAMMABLE.