



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
TT-E-485F COMP.G

PRODUCT: A rust inhibiting semigloss enamel formulated to meet TT-E-485F Comp.G specification.

DESCRIPTION: *TT-E-485F Composition G* is a semigloss rust inhibiting enamel for use on metal as a one or two coat primer/finishing coating system available in four types.
TYPE I: Dip Application
TYPE II: Brush & Roller Application
TYPE III: Roller Coat Application
TYPE IV: Flash Dry Application

PROPERTIES: COLOR..... #24084 Olive Drab
FINISH..... Semi-Gloss
SOLIDS(Weight)..... 56 - 75%
PIGMENT(Weight)..... 30 - 55%
VISCOSITY(#4 Ford Cup)..... 75 - 200 Sec.

DRYING TIMES:
TO TOUCH..... Within 3 Hours
DRY THROUGH..... Within 16 Hours
DRY HARD..... Within 72 Hours

ADVANTAGES: (1). Rust Inhibiting
(2). Primer / Topcoat System
(3). Resistant to Abrasion
(4). Air Dry

USE: Properly prepared metal surfaces.

APPLICATION: Apply by brush, roller or spray methods. For brush and roll, thin with MIL-T-81772B Type III up to one pint per gallon. For spray application, thin with MIL-T-81772B Type III at 10-15% by volume or for proper atomization.