



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
TT-L-26C
LACQUER

PRODUCT: This specification covers an industrial grade clear and pigmented gloss lacquer for brush application. This product is recommended for interior or exterior use on primer metal or sealed wood surfaces. The clear lacquer can be used directly on copper and brass surfaces without priming. Meets government specification TT-L-26C.

PROPERTIES: COLORS..... All Fed-Std 595B
GRIND..... N/A
SPECULAR GLOSS..... FULL
VISCOSITY #4 Ford Cup..... 27 TO 40 Sec.

DRYING TIME AT 75 DEGREES F:

DUST FREE: 15 MINUTES MAX.
DRY THROUGH: 2 HRS. MAX.

USES:

- (1). Machinery
- (2). Copper or Brass
- (3). Steel Surfaces
- (4). Equipment
- (5). Sealed wood

CONTENTS ARE FLAMMABLE.

KEEP AWAY FROM HEAT AND OPEN FLAME.

KEEP OUT OF THE REACH OF CHILDREN.

DO NOT TAKE INTERNALLY

AVOID BREATHING VAPOR OR MIST.

DO NOT USE IN TANK OR PIT WITHOUR PROPER PROTECTION.

READ MATERIAL SAFETY DATA SHEET BEFORE USE OF THIS PRODUCT.