



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET TT-L-50G

PRODUCT: An air dry acrylic lacquer in aerosol cans or bulk.

DESCRIPTION: *Intrepid's TT-L-50G Type I Nitrocellulose Lacquer or Type II Acrylic* is a high grade lacquer coating supplied in pressurized dispensers or bulk for general purpose applications. A full range of colors is available including clear.

PROPERTIES: COLORS..... Clear & Full Range
FINISH..... Flat - High Gloss
SOLIDS(Weight)..... 40 - 64%
FINESS OF GRIND..... 5 - 7

DRYING TIMES:

DUST FREE..... 5 Minutes
DRY HARD..... 10 Minutes
DRY THROUGH..... 2 Hours

ADVANTAGES: (1). Fast Dry
(2). Acrylic Resin
(3). Durable
(4). Air Dry

USES: (1). Metal
(2). Wood
(3). Paper
(4). Tools
(5). Garden Implements

APPLICATION: Vigorously shake can for one minute to thoroughly mix coating. Shake can occasionally while spraying. Hold aerosol can approximately 12" from surface to be painted. Non-aerosol bulk form can be applied by conventional or airless spray application. For spraying, thin up to 10% or as needed with MIL-T-81772B TY.3 Thinner. For brushing, reduce up to 10% with MIL-T-81772B TY.3 Thinner. Brush small areas only.

READ MSDS BEFORE USE.