



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
ACID RESISTANT LACQUER
TT-L-54C

PRODUCT: An acid, gasoline and oil resistant lacquer formulated for spraying the aluminum surface around storage batteries.

DESCRIPTION: **TT-L-54C ACID RESISTANT LACQUER** is a spraying lacquer specifically formulated for use on the aluminum surface around storage batteries. This coating is resistant to acid, gasoline and oils. Formulated for spraying, however, small areas may be brushed if spraying is impractical.

PROPERTIES:

COLORS:

FINISH..... High Gloss

SOLIDS(Weight)..... 28 - 33%

DRYING TIMES:

TO TOUCH..... 10 Minutes

DRY HARD..... 60 Minutes

ADVANTAGES:

- (1). Acid Resistant.
- (2). Gasoline Resistant.
- (3). Oil Resistant.
- (4). Durable.
- (5). Fast Dry.

USES:

- (1). Auto/Truck Battery Trays.
- (2). Battery Storage Racks.
- (3). Engine Racks.

APPLICATION: Apply by spray method, although small areas may be brushed. Thin with MIL-T-81772B Type III Reducer or A-A-857B at approximately 10% by volume or as required for proper atomization for spraying. For brushing, thin as needed to facilitate proper flow. Do not over brush.