



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
TT-S-300A TY. I
GRADE B, BODY 2 (4.5#)
BLEACHED SHELLAC
PAGE 1 OF 1

PRODUCT: A shellac varnish for use as a protective coating for many purposes. Available in Type I, Clear (Bleached), and Type II Orange finishes.

PROPERTIES:

DRYING TIME:

DRY TO TOUCH..... Within 15 Minutes
DRY HARD..... Within 60 Minutes
SHELF LIFE..... 1 Year

SURFACE PREPARATION:

Surface to be coated must be clean, dry, and free of all foreign contaminants including grease, oil, dirt and paint. Remove wax from wood surfaces with mineral spirits before application. This product may be applied by brush, wiping, or spray application. Thin and clean up with denatured alcohol

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN.
KEEP AWAY FROM HEAT AND OPEN FLAME.
DO NOT TAKE INTERNALLY.
USE WITH ADEQUATE VENTILATION.
AVOID BREATHING VAPOR OR MIST.
AVOID CONTACT WITH SKIN AND EYES.
DO NOT USE IN TANK OR PIT WITHOUT PROPER PROTECTION.
READ MATERIAL SAFETY DATA SHEET BEFORE USING.
CONTENTS ARE FLAMMABLE.