



**Intrepid Coatings**

**“Our Coatings Fly All Over the World”**

# **Intrepid Coatings, Inc. Technical Data Sheets**

## **Miscellaneous Coatings**

**Intrepid Coatings**  
1910 East Riverview Drive  
Phoenix, AZ 85034  
Phone: (602)243-3293  
Fax: (602)268-6801  
E-Mail: [info@intrepidcoatings.com](mailto:info@intrepidcoatings.com)

**TECHNICAL DATA SHEET**  
**100% ACRYLIC LATEX 300G02**  
**GRASS GREEN CONCENTRATE**  
**PAGE 1 OF 2**

**PRODUCT:** A water-base, 100% acrylic latex grass tint in concentrate form.

**DESCRIPTION:** A waterbase 100% acrylic base, grass tint concentrate for use on dormant lawns. This material can be reduced with water at a ratio of 10 parts water to 1 part concentrate all the way up to 22 parts water to 1 part concentrate depending on operator preference. This grass tint is waterbase and contains no lead or chromates. Color is a pleasing, natural green tint that duplicates the richness of a lawn or turf that is fade resistant due to acrylic latex resin base. Fast dry properties reduce tracking and staining after application.

**PROPERTIES:**

COLOR.....	Grass Green
SOLIDS(Weight).....	49 - 51%
SOLIDS(Volume).....	31 - 32%
REDUCTION.....	10:1 - 22:1
VEHICLE TYPE.....	Modified Acrylic Latex
WEIGHT/GAL.....	11 - 11.5#

**ADVANTAGES:**

- (1). Low Volatile Organic Compound Content.
- (2). Excellent Exterior Durability.
- (3). Fast Dry - Water Reducible
- (4). Weather and UV Resistant.
- (5). Lead & Chromate Free.
- (6). Highly Concentrated.
- (7). High Solids.

**USES:**

- (1). Soccer Fields.
- (2). Cemeteries.
- (3). Residential Lawns.
- (4). Turfs.
- (5). Golf Courses.

**TECHNICAL DATA SHEET**  
**100% ACRYLIC LATEX 300G02**  
**GRASS GREEN CONCENTRATE**  
**PAGE 2 OF 2**

**APPLICATION & REDUCTION:**

Green Grass Concentrate Tint can be reduced from 10 parts water to 1 part concentrate up to 22 parts water to 1 part concentrate depending on operator preference. After dilution, material can be applied with a garden type pump pressure sprayer or airless paint rigs. For best results, grass should be dry before application to avoid further dilution and to aid absorption and dry time.

**PRECAUTIONS:**

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.

KEEP FROM FREEZING.

**TECHNICAL DATA SHEET**  
**500V02 DUAL-ETCH**

**PRODUCT DESCRIPTION:**

A multi-purpose metal cleaner, prepaint conditioner and rust remover. This product is formulated for use on ferrous metals, including steel. It will also remove light rust from chrome-plated substrates.

**TYPICAL PROPERTIES:**

- (1). **SOLVENT**..... Inorganic Acids
- (2). **VISCOSITY**..... Water-like
- (3). **FINISH**..... Clear liquid pretreatment

**DIRECTIONS FOR USE:**

Solution is ready for use as packaged. No dilution is necessary. Freely apply Dual-Etch with brush, mop or synthetic sponge to the substrate. Use steel wool on heavy rust and oily deposits until they have been dissolved. Always keep the surface wet while scrubbing with rag or steel wool. While surface is wet, flush well with water or rub down surface with rags that have been periodically rinsed in clean water until all residue is removed. Allow surface to dry before applying paint.

**PRECAUTIONS:**

AVOID CONTACT WITH SKIN, EYES OR CLOTHING.

**CONTAINS ACID**, USE PROPER SKIN & EYE PROTECTION.

USE WITH ADEQUATE VENTILATION.

KEEP OUT OF THE REACH OF CHILDREN.

IN CASE OF IRRITATION, FLUSH WITH LARGE AMOUNTS OF WATER.

**READ MATERIAL SAFETY DATA SHEET BEFORE USING THIS PRODUCT.**

**TECHNICAL DATA SHEET  
EPOXY CRACK FILLER**

**PRODUCT:** A liquid modified 100% solids epoxy coating with room temperature curing. Excellent adhesion to concrete and other materials. This coating will cure in the presence of moisture.

**MAJOR USES:** Patching and surfacing, patching compounds, adhesives, bonding new and old concrete, potting and encapsulation, casting, hand lay laminating and seamless floors.

**PROPERTIES:** 100% solids  
Tensile strength..... 400 - 500  
PSI  
Tensile elongation..... D-  
638  
Pot life at 77 F..... 15 - 35 minutes  
Chemical and acid resistance..... Excellent

**APPLICATION:** Griggs Epoxy Crack Filler is supplied in kits that yield 1 gal. This material can be poured directly into the crack. Always remember to mix Part A with Part B. It is very important to mix both parts well before use. Also very important is the thorough mixing after combining part A with part B.

**PRECAUTIONS:** Take these precautions before the coating dries and during application.

**The following applies to Part A and Part B**

Harmful or fatal if swallowed. Vapor harmful. Eye irritant. Keep away from heat, sparks, and open flame. Avoid prolonged contact with skin or breathing of vapors. Keep containers closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

Use with adequate ventilation. KEEP OUT OF REACH OF CHILDREN!!! If swallowed do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY.

**TECHNICAL DATA SHEET**  
**4606-100 EPOXY**  
**PAGE 1 OF 3**

**PRODUCT:** A liquid modified 100% solids epoxy coating.

**DESCRIPTION:** ICS 4606-100 Epoxy Coating is a two-component epoxy coating that contains an extremely high solids content. When fully cured, it forms an extremely tough, glossy, blush-free film that exhibits excellent impact and abrasion resistance. The cured film is unaffected by grease, oil, gasoline, detergents, and most solvents. This epoxy coating is formulated to cure in the presence of moisture. ICS 4606-100 Epoxy Coating can be applied at any mil thickness in a single application due to its high solids content. This coating may be made into a non-skid film by the addition of silica sand or any desired aggregate.

**MAJOR USES:** ICS-4606 100 Epoxy Coating can be used for concrete flooring and walls of containment reservoirs and seamless floors in garages carports, factories, warehouses and industrial facilities, sewage and waste treatment plants, water treatment plants.

**PROPERTIES:**

SOLIDS(Volume).....	100%
TENSIL STRENGTH.....	9500-10000 PSI
TENSIL ELONGATION.....	6-7
COLOR.....	Light Gray
POT LIFE(77 degrees F).....	1-2 Hours*
TACK FREE.....	7 Hours*
RECOAT.....	Overnight*
LIGHT SERVICE.....	24 Hours*
FULL SERVICE.....	5 Days*
GLOSS.....	Full Gloss
VOC.....	0

\*Higher temperatures will accelerate dry times and decrease pot life, lower temperatures will lengthen cure times and slightly increase pot life.

**TECHNICAL DATA SHEET**  
**4606-100 EPOXY**  
**PAGE 2 OF 3**

**SURFACE PREPARATION:** Surface to be coated must be clean, structurally sound and free of all foreign contaminants including dirt, wax, loose paint or curing compounds. Surface may be damp, but standing water must be removed. Concrete should be sandblasted (whip blast). If recoating an epoxy surface is desired, and coating has cured more than 24 hours at 77 degrees F or cannot be indented with a fingernail, a light sanding with 60 80 grit sandpaper is required for proper adhesion of the new coat.

**MIXING INSTRUCTIONS:** This material is 100% solids with high viscosity. Mix only that amount of material that can be used in a 2 Hour work period at 77 degrees F. Work times are shortened by higher temperatures. For longer pot life(work life) pour mixed material on floor immediately after mixing. Always carefully measure the amounts and mix for 2 full minutes using a wooden stir stick, scraping the bottom and sides of the mixing vessel. Thorough mixing of the material is very important for obtaining a properly cured film.

**APPLICATION RECOMMENDATIONS:** ICS 4606-100 EPOXY COATING can be applied by brush, roller, notched trowel or airless spray. It is normally applied as received. For application of high build protective coatings to concrete, normal spread rate is 200-300 square feet per gallon. At this spread rate, a dry film thickness of 6-8 mils and a uniform glossy film will be achieved. Application is most easily achieved by pouring the admixed material on the floor, brush trimming the edges and seams and spreading the material with a short nap or carpet roller. Backroll sufficiently to insure a good even distribution of the coating. If a non-slip surface is desired, walk back onto the **uncured** coating wearing golf shoes and sprinkle silica sand from a shaker can into the coating and roll it in with a short nap or carpet roller. When airless equipment is used, a 45 to 1 pump and .022" to .030 tip is recommended. DO NOT LET ADMIXED MATERIAL REMAIN IN OR ON APPLICATION EQUIPMENT LONGER THAN 2 HOURS.

**TECHNICAL DATA SHEET**  
**4606-100 EPOXY**  
**PAGE 3 OF 3**

**PRECAUTIONS:**

USE WITH ADEQUATE VENTILATION.

KEEP OUT OF THE REACH OF CHILDREN.

USE WITH PROPER DUAL CARTRIDGE RESPIRATOR WITH GREEN BAND CARTRIDGE TO PROTECT AGAINST METHYL AMINE VAPORS.

AVOID SKIN CONTACT, WEAR PROTECTIVE GLOVES.

WEAR SAFETY GLASSES OR GOGGLES.

DO NOT BREATHE VAPORS.

READ MATERIAL SAFETY DATA SHEET BEFORE USING THIS COATING.



**TECHNICAL DATA SHEET**  
**4606 PATCH EPOXY**  
**PAGE 1 OF 2**

**PRODUCT:** A liquid modified 100% solids epoxy coating with room temperature curing. Excellent adhesion to concrete and other surfaces.

**MAJOR USES:** Patching, filling joints and cracks, surfacing ramps and other industrial areas that require a non skid surface.

**PROPERTIES:** 100% solids  
*Cure Time:*  
Light Traffic..... 4-12 hours  
Heavy Traffic..... 12-24 hours  
Resistant to..... Chemicals,  
Cleaning Solvents and Soaps, Jet Fuels,  
Degreasers and Solvents,

**SURFACE PREPARATIONS:**

The minimum cure time of concrete must be least 30 days before application of 4606 Patch Epoxy (concrete shrinks during the normal curing process and may continue to shrink and settle after the 30 day curing period). Ambient & surface temperature of substrate must be above 50 degrees F. for proper curing of 4606 Patch Epoxy. The crack or joint should be dry and free of all loose debris, dirt, dust, curing compounds, release agents and other contaminants to produce a sound surface before application of 4606 Patch Epoxy.

**MIXING:**

Mix Component A & B until all pigments and settlement are completely mixed in before combining the two components. Then slowly pour component B into component A mixing slowly. Mixed admixed material 1-2 1/2 minutes until completely mixed (if components A & B are not completely mixed this will severely effect the curing process of 4606 Patch Epoxy). Manual or mechanical mixing may be used to mix 4606 Patch Epoxy. Dispense admixed material and clean tools immediately

**TECHNICAL DATA SHEET**  
**4606 PATCH EPOXY**  
**PAGE 2 OF 2**

(cleaning may be done with T-262 Epoxy Thinner or a good Lacquer Wash). To extend the pot life of 4606 Patch Epoxy components A & B may be inserted into a freezer or ice bath before mixing the 2 components with each other.

**APPLICATION:** 4606 Epoxy Crack Filler is supplied in kits. This material can be poured directly into the crack or applied with a bulk dispensing caulking gun. Always remember to mix Part A with Part B. It is very important to mix both parts well before use. Also very important is the thorough mixing after combining part A with part B. 4606 Patch Epoxy should be applied to joints and cracks in 2 stages. The first stage should fill the crack or joint approximately half the distance to the surface. Allow the first stage to settle 15 to 30 minutes then apply second stage until flush with the surface. All 4606 Patch Epoxy is filled over the surface should be shaved until flush with the surface.

**PRECAUTIONS:** Take these precautions before the coating dries and during application.

**The following applies to Part A and Part B**

Harmful or fatal if swallowed. Vapor harmful. Eye irritant. Keep away from heat, sparks, and open flame. Avoid prolonged contact with skin or breathing of vapors. Keep containers closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

CAUTION: Admixed material may reach temperatures above 150 degrees F. Use with adequate ventilation. KEEP OUT OF REACH OF CHILDREN!!! If swallowed do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY.

**TECHNICAL DATA SHEET  
BOILED LINSEED OIL**

**PRODUCT DESCRIPTION:**

A 100% pure boiled linseed oil for use on wood furniture or as an additive to oilbase enamels.

**TYPICAL PROPERTIES:**

- (1). **WEIGHT PER GALLON**..... 7.82 - 7.85
- (2). **SPECIFIC GRAVITY**..... .942 - .943
- (3). **PERCENT VOLATILE BY VOLUME**..... 0%
- (4). **FLASH POINT**..... GREATER THAN 200 F

**DIRECTIONS FOR USE:**

Use as a sealer and enhancer for wood and wood furniture. May also be used in some types of oilbase alkyd coatings to slow drying time and increase flow and leveling.

**TECHNICAL DATA SHEET  
EPOXY/POLY ANTI-GRAFFITI  
HI-BUILD  
PAGE 1 OF 2**

**PRODUCT:** A two-component epoxy-modified polyurethane anti-graffiti coating system.

**DESCRIPTION:** Griggs Epoxy-Modified Polyurethane coating is a high solids chemically cured product that forms a film that is resistant to chemicals, solvents and abrasion. This product has excellent adhesion to most substrates and is designed to seal and protect all masonry surfaces against many types of graffiti and weathering. This coating is available in a 4:1 mixture for spray, brush and roll applications. It has a high solids content for excellent film build and low volatile organic compound content. A two coat system is recommended for proper protection. Apply first coat in order to seal the surface, second coat is applied to achieve a proper film build for protection.

**PROPERTIES:**

SOLIDS(Weight).....	63 - 68%
SOLIDS(Volume).....	53 - 56%
VISCOSITY.....	70 - 90 KU
COLORS.....	Full Range
POT LIFE(77 degrees F).....	6 - 8 Hours*
TACK FREE.....	3 - 4 Hours*
RECOAT.....	Overnight*
LIGHT SERVICE.....	24 Hours*
FULL SERVICE.....	7 Days*

\* Higher temperatures will accelerate dry times and decrease pot life, lower temperatures will lengthen cure times and slightly increase pot life.

**TECHNICAL DATA SHEET**  
**EPOXY/POLY ANTI-GRAFFITI**  
**HI-BUILD**  
**PAGE 2 OF 2**

**SURFACE PREPARATION:** Surface to be coated must be clean, dry, and free of all foreign contaminants including grease, oil, dirt and loose paint or curing compounds. Dirt and dust are best removed with a stiff bristle brush and by compressed air. Grease and oil should be removed by cleaning with appropriate solvents such as mineral spirits, lacquer wash thinner or xylene. New masonry and concrete surfaces must be cured a minimum of 28 days before application. Prepare cement and concrete surfaces by acid washing with a solution of 1 part muriatic acid to 4 parts water. Always pour the acid into the water to avoid splattering. Pour onto cement surface, broom or brush in with a stiff bristle brush in order to achieve proper etching. Flush thoroughly with clean water, neutralize any remaining acid with a solution of ammonia and water, flush again with clean water. Let dry thoroughly.

**APPLICATION:** Mix 4 parts Component 1 to 1 part Component 2 by volume. Thin first coat up to 50% by volume(2-qts per gal/kit) to achieve proper penetration on bare masonry surfaces. Apply second coat with minimum thinning(up to 1-qt per gal/kit) for proper film build. Thin with Griggs Epoxy/Poly Reducer. This coating may be applied by brush, roll or spray methods.

**PRECAUTIONS:**

KEEP FROM REACH OF CHILDREN.

KEEP AWAY FROM HEAT, SPARKS OR FLAME.

USE WITH ADEQUATE VENTILATION.

AVOID BREATHING VAPOR OR MIST.

READ MATERIAL SAFETY DATA SHEET BEFORE USING.

**TECHNICAL DATA SHEET  
GRIGGS EPOXY LOOP SEALANT**

**PRODUCT:** A viscous, two component, liquid epoxy for inductive loops.

**DESCRIPTION:** Griggs Epoxy Loop Sealant is a high viscosity liquid epoxy formulated for use in sealing inductive wire loops and leads imbedded in asphalt, concrete and portland cement concrete for traffic signal controls and vehicle counters. This epoxy is used for repair work on existing spalls, cracks, and other deformations in and around saw cuts housing inductor loops and leads. The rapid cure allows minimum traffic delay. This sealant is suitable for use in freeze-thaw areas and can be used on grades up to 15 percent without excessive flow of material.

**DIRECTIONS FOR USE:** Saw cuts shall be blown clean and dry with compressed air to remove all excess moisture and debris. For repairing damaged saw cuts, all loose spalled material shall be cleaned away from saw cut, chipping back to sound asphalt concrete or portland cement concrete and all loose material cleaned from loop wires.

The mixing ratio is approximately 8.4# Component A to 1.4# Component B. Due to the impracticality of this ratio, packaging is premeasured. Open the resin Component "A" (the larger gallon can) and stir to reblend any settlement. If possible, pour into a larger mixing container such as a five gallon plastic pail. Add hardener can "B" and begin to slowly mix. Mix for 2 1/2 to 3 minutes until thoroughly blended with no streaking. No more material shall be mixed than can be used within 10 minutes from the time mixing operations are started.

**CHARACTERISTICS:**

Gel Time.....	13-18 minutes
Tensile Strength.....	400 psi(min)
Elongation.....	90%(min)
Shore D Hardness.....	45(min)

**TECHNICAL DATA SHEET**  
**JM-3 STRIPPER**

**PRODUCT DESCRIPTION:**

A mildly acidic viscous liquid paint remover developed especially for removing epoxy, polyurethane and other difficult industrial paint coatings from metal surfaces. Griggs JM-3 Stripper has long storage stability and excellent rinsing properties. It is not intended to be used in removing paint coatings from magnesium.

**USAGE:**

Griggs JM-3 Stripper comes ready to use and may be applied directly to metal surfaces. It may be sprayed, brushed or mopped onto the metal surfaces needing to be stripped of the paint coating. Do not use synthetic brushes. A natural bristle type is recommended. Apply JM-3 and allow to dwell for 15 to 30 minutes. When coating begins to blister, brush into a slurry and rinse with a pressure washer or steam gun. Slight rubbing while rinsing helps insure complete removal of paint residues.

**WARNINGS AND PRECAUTIONS:**

Griggs JM-3 Stripper contains methylene chloride and phenol. Use with adequate ventilation. JM-3 has a sharp acidic odor. Keep off skin and out of eyes. Keep away from heat, sparks and flame. Keep container tightly closed. For industrial use only. Read MSDS before using this product. Wear goggles and neoprene gloves when using this product. Keep out of reach of children.

**TECHNICAL DATA SHEET  
LITOXO SEALER****PRODUCT DESCRIPTION:**

Litoxo Sealer is formulated for corrosion control of magnesium and other metals.

**TYPICAL PROPERTIES:**

- (1). **COLORS**.....Yellow and Green
- (2). **ELONGATION:**  
Passes 1/8" conical mandrel method per ASTM D-522-60.
- (3). **WATER IMMERSION:** No blistering, cracking, softening or delamination of film. No corrosion after 140+ hours in salt water 5% solution ASTM-B117.
- (4). **MEK RUB:** 100+ per ASTM D-740, PASSED
- (5). **IMPACT TEST:** Direct and reverse, 40 pounds, ASTM G-14 (06.01), PASSED.
- (6). **CROSS HATCH TEST:** 100%, ASTM D3359, PASSED
- (7). **FALLING SAND TEST:** OTTAWA SAND 20-30 MESH, ASTM D 968-81 METHOD A, PASSED.
- (8). **HOT OIL TEST:** MIL-L-7808 48 HOURS @ 300 oF, PASSED
- (9). **PENCIL HARDNESS:** 4H
- (10). Excellent Solvent, Chemical, Water & Heat Resistance.
- (11). Cures within 30 minutes at 350 degrees F.
- (12). Excellent Corrosion Resistance
- (13). **WEIGHT/GAL:** 10.1 lbs/gal
- (14). **SOLIDS(Volume):** 44-46%
- (15). **SPRAYING VISCOSITY:** 14-20 Seconds #2 Zahn Cup.

**APPLICATION AND REDUCTION:**

- (1). Allow part to cool if masking is required. High temperature tape shall be used.
- (2). Place part in oven and heat to 350 degrees F for 30 minutes.
- (3). Cool substrate to room temperature.
- (4). Adjust spray or dip consistency with T-60 Thinner. Use a minimum of 2 qts T-60 per gallon of Litoxo.
- (5). Coat all surface, both exterior and interior, to a thickness of .50 to 1.0 dry mil.
- (6). Air dry coating for 25-30 minutes, then bake in a **preheated** oven at 350 degrees F for 30 minutes minimum. Cool parts to room temperature and unmask as necessary.



**TECHNICAL DATA SHEET  
M-Y-R-A ADHESIVE EPOXY**

- PRODUCT:** A liquid modified 100% solids epoxy coating with room temperature curing. Excellent adhesion to concrete and other materials. This coating will cure in the presence of moisture.
- MAJOR USES:** Flooring and surfacing, patching compounds, adhesives, bonding new and old concrete, potting and encapsulation, casting, hand lay laminating and seamless floors.
- PROPERTIES:** 100% solids  
Tensile strength: 8,000 - 10,000 P.S.I. Tensile elongation: 6 - 7 Pot life at 77 F: 10 30 minutes. Chemical and acid resistance: Excellent (see manufacture for more details)
- APPLICATION:** MYRA Adhesive Epoxy is supplied in kits that 1 or 5 gallons. This material can be rolled, squeegeed and brushed with proper tools. Mix part A with part B. It is very important to mix both parts well before use. Also very important is the thorough mixing after combining part A with part B. For longer pot life we suggest that after mixing well, admixed material be spread immediately to substrate. The thinner the mil the longer the pot life.
- COLORS:** Concrete Gray, some pastel colors upon request.
- PRECAUTIONS:** Take these precautions before the coating dries and during application. **The following applies to Part A and Part B** Harmful or fatal if swallowed. Vapor harmful. Eye irritant. Keep away from heat, sparks, and open flame. Avoid prolonged contact with skin or breathing of vapors. Keep containers closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.  
Use with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN!!!** If swallowed do not induce vomiting. **CALL A PHYSICIAN IMMEDIATELY**

**TECHNICAL DATA SHEET**  
**TT-W-00572 TYPE SEALER**  
**PAGE 1 OF 2**

- PRODUCT:** A clear, non-yellowing sealer formulated to meet Federal Specification TT-W-00572.
- DESCRIPTION:** Griggs TT-W-00572 clear sealer is a water repellent, penetrating sealer that will provide protection to any wood or concrete surface or structure. Due to its superior penetrating properties, it exhibits excellent adhesion to properly prepared substrates. This product is available in a full range of semi-opaque colors.
- PROPERTIES:**
- |                     |               |
|---------------------|---------------|
| COLORS.....         | Full Range    |
| FINISH.....         | Penetrating   |
| VEHICLE.....        | Butene Rubber |
| SOLIDS(Volume)..... | 12 - 16%      |
| WEIGHT/GAL.....     | 6.5 - 6.8#    |
| VISCOSITY.....      | 150 - 500 CPS |
- DRYING TIMES:**
- |               |         |
|---------------|---------|
| TO TOUCH..... | 2 Hours |
|---------------|---------|
- ADVANTAGES:**
- (1). Highly Durable.
  - (2). Ultraviolet Resistant.
  - (3). Penetrating.
  - (4). Oil Resistant.
- USES:**
- (1). Concrete Structures.
  - (2). Driveways.
  - (3). Wood.
  - (4). Railroad Ties.
  - (5). Plywood.
  - (6). Walkways.

**TECHNICAL DATA SHEET**  
**TT-W-00572 TYPE SEALER**  
**PAGE 2 OF 2**

**APPLICATION:** Apply by brush, roller or spray methods. Use at packaged viscosity for all application methods. Clean up with Mineral Spirits.

**PRODUCT:** A clear, penetrating wood and concrete sealer.

**SURFACE PREPARATION:** All surfaces must be clean, dry and free of all dirt, dust, grease or any foreign contaminants. For concrete, sandblasting is the most efficient method. If this is impossible, acid etch with a 25% solution of Muriatic Acid, neutralize with an ammonia solution and let dry thoroughly. Do not apply at temperatures below 50 degrees Fahrenheit.

**PRECAUTIONS:** Use with adequate ventilation.

Avoid contact with skin and eyes.

Do not take internally.

**KEEP OUT OF THE REACH OF CHILDREN.**

Vapor Harmful.

Wash hands after using.

**TECHNICAL DATA SHEET  
WATERBASE POOL PAINT  
PAGE 1 OF 2**

**PRODUCT:** A water-reducible, rubber based swimming pool paint designed to withstand continuous submersion.

**DESCRIPTION:** A waterbase swimming pool paint that is formulated using Goodyear rubberized resin. This coating is water thinnable, low-odor and meets air pollution regulations for Volatile Organic Compounds.

**PROPERTIES:**

COLORS.....	Full Range
GRIND.....	Not Under 5
GLOSS.....	Flat & Gloss
VISCOSITY.....	100 - 110 KU
<b>DRYING TIME-AT 75 DEGREES F:</b>	
SET-TO-TOUCH.....	Within 1 Hour
RECOAT TIME.....	4 Hours
PVC.....	54%
SOLIDS(Weight).....	66%
SOLIDS(Volume).....	48%

**ADVANTAGES:**

- (1). Water Clean-Up
- (2). Water Reducible
- (3). Low Odor
- (4). Meets VOC Regulations
- (5). Fast Dry

**USES:**

- (1). Swimming Pools
- (2). Fountains
- (3). Concrete
- (4). Plaster
- (5). Ponds
- (6). Reflection Basins

**TECHNICAL DATA SHEET  
WATERBASE BASE POOL PAINT  
PAGE 2 OF 2**

**APPLICATION & REDUCTION:**

Griggs Waterbase Rubber Pool Paint can be applied by brush, roller or airless spray application. For spraying, thin up to 10% or as needed with Water. For brush and roll use as is or with minimum thinning.

**SURFACE PREPARATION:**

Surface must be clean, and free of all contamination before application. Etch surface for best results. Surface may be damp but not wet prior to application. Consult your Griggs representative for specific surface preparation instructions. Allow 7 - 10 days of dry weather before filling pool. For each day of rain, allow 2 additional days of drying. Do not apply if rain threatens.

**PRECAUTIONS:**

KEEP FROM FREEZING.

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.

## Index

### #

#356 Polyurethane, 707  
#4606 100% Solids Epoxy, 387  
#4606 Patch Epoxy, 389

### 1

10% Polyurethane Accelerator, 498  
100% Acrylic Emulsion VOC Free, 167  
100% Acrylic Gloss Enamel, 177  
100% Acrylic HD Block Filler, 33  
100% Acrylic Latex, 2, 89, 109, 161  
100% Acrylic Latex #1018, 230  
100% Acrylic Latex Bug Stop Formula, 121  
100% Acrylic Latex Elastomeric Textured Coating, 232  
100% Acrylic Latex Exterior, 234  
100% Acrylic Latex Flat, 19, 91, 93, 236  
100% Acrylic Latex Gloss, 35, 95  
100% Acrylic Latex Grass Green Concentrate, 1336  
100% Acrylic Latex Interior, 107  
100% Acrylic Latex Interior Gloss, 37  
100% Acrylic Latex Masonry Filler, 238  
100% Acrylic Latex Mildew Resistant, 97  
100% Acrylic Latex Non-Sand Elastomeric Textured Coating, 240  
100% Acrylic Latex Pearlescent Pigment, 242  
100% Acrylic Latex Semigloss, 62, 99, 123  
100% Acrylic Latex Semigloss Super Acrylic Series, 56  
100% Acrylic Latex Textured Coating, 77  
100% Acrylic Primer, 1253  
100% Acrylic Stain, 101  
100% Solids Conductive Epoxy, 392  
100% Solids Epoxy, 396, 709  
100% Super Acrylic Latex, 171

### 3

3-1 Stainout, 113, 244  
36-603 Hi-Heat Coating, 712

### 4

4606 Patch Epoxy, 713, 1343  
4606-100 Epoxy, 716, 1340

### 6

611BC Epoxy Amine Gloss Green Primer, 1155  
611BC Epoxy Gloss Green Primer/Topcoat, 1147  
611BC NPC61611 Epoxy Amine Coating Gloss Green, 719  
612A Epoxy #34151 Green Primer, 1257  
612A Epoxy Amine #34151 Green Primer, 1149

612A Epoxy Polyamine #34151 Green Primer, 1255

### 8

8865 Containment Epoxy Coating, 372, 599

### A

A-423-66 Cati-Coat Epoxy Amine Coating, 720  
A-423-66 Epoxy Amine Coating, 721  
A-423-66 Epoxy Amine Coating #082 Munsell Blue, 705  
A-423-66 Epoxy Amine Coating #17038 Gloss Black, 703  
A-423-66 Epoxy Amine Coating Clear, 704  
A-423-66 NPC61600-2 Epoxy Amine Coating, 722  
A-423-66 NPC61624, NPC61678 Epoxy Amine Coating #16492 Gray, 706  
A-932-66 Epoxy Enamel, 723  
A-A-1452B Acid Resistant Lacquer, 724  
A-A-1558A Stencil Paint, 725  
A-A-1572 Lacquer Sanding Sealer, 1194  
A-A-2246 Type I, Class 2, Latex Interior, 225  
A-A-2246B Type I, Class 4, Latex Interior, 226  
A-A-2336 Wood Primer, 1093  
A-A-2787 Type I, Low VOC Aerosol Enamel, 726  
A-A-2886A Type I, Traffic Paint, 399  
A-A-2904 Mineral Spirits, 1327  
A-A-2962 Type I, Class A, Alkyd Enamel Semigloss, 652  
A-A-2962 Type I, Class A, Grade B, Alkyd Enamel Semigloss, 727  
A-A-2962A Class A, Grade B, Alkyd Enamel Semigloss, 642  
A-A-2962A Type I, Class B, Lusterless Alkyd Enamel, 664  
A-A-2962A Type III, Class B, Alkyd Enamel Gloss, 728  
A-A-3003 Spraying Lacquer, 729  
A-A-3121 Rubberized Deck Enamel, 401  
A-A-3164 Synthetic Lacquer, 731  
A-A-3165 Lacquer Coating Gloss, 733  
A-A-50574 Alkyd Enamel Semigloss, 223  
A-A-59166 Walkway Compound Nonslip, 735  
A-A-665E Fast Dry Aerosol Enamel, 736  
A-A-857B Dope and Lacquer Thinner, 1323  
Able Ratmoore Series, 968  
Acrylic Abatement Coating, 75  
Acrylic Block Filler, 105  
Acrylic Coating Exterior, 342, 344, 346, 348, 352  
Acrylic Enamel, 541, 737  
Acrylic Enamel Interior, 246  
Acrylic Enamel Primer, 942  
Acrylic Hi-Gloss Latex Enamel, 175  
Acrylic Pool Deck Coating, 326  
Acrylic Lacquer Very Low VOC, 701  
Acrylic Latex Flat, 145, 147  
Acrylic Latex Flat Exterior, 149  
Acrylic Latex Flat Interior/Exterior, 151  
Acrylic Latex Primer, 69, 117, 1139

## Index (continued)

Acrylic Latex Semigloss, 4  
Acrylic Latex Semigloss Enamel, 125, 127, 137  
Acrylic Latex Stain, 103  
Acrylic Masonry Stain, 209, 248  
Acrylic Masonry Stain/Sealer, 356, 403, 405  
Acrylic Primer, 990  
Acrylic Urethane Enamel, 530  
Acrylic Urethane Varnish, 23  
Acrythane Acrylic Polyurethane, 739  
ADOT #1 Alkyd Light Gray Primer, 964  
ADOT #1 Phenolic Light Gray Primer, 966  
ADOT #2 Off White, 15  
ADOT #2 Off White Primer, 1083  
ADOT #3 Hydro-Acrylic Aluminum Topcoat, 511  
ADOT #3 Hydro-Acrylic Coating, 521  
ADOT #3 Silicone Alkyd Enamel, 250, 743  
ADOT #3 Topcoat Gloss, 741  
ADOT #5 Aluminum, 548  
ADOT #5 Hydro-Acrylic Aluminum Topcoat, 513  
ADOT Hydro-Acrylic Primer, 1123, 1127, 1129, 1131  
Alkyd Ceiling Enamel, 215  
Alkyd Chalk-Bond Clear Primer, 1011, 1013  
Alkyd Chalk-Bond Primer White, 1113  
Alkyd Dipping Advance Gray Primer, 997  
Alkyd Dipping Primer Advance Gray, 507  
Alkyd Enamel High Gloss, 589, 745  
Alkyd Enamel High Gloss Exterior, 591  
Alkyd Enamel High-Gloss, 217  
Alkyd Enamel Oilbase, 252  
Alkyd M. W. Gray Primer, 1001  
Alkyd Metal Primer, 944  
Alkyd Metal Undercoat, 1105  
Alkyd Primer Interior/Exterior, 254  
Alkyd SSP 25 Lee Gray Primer, 1007  
Alkyd Trim Enamel, 211  
Alkyd Undercoat Interior, 1107, 1258  
Alkyd Undercoat Interior/Exterior, 1087  
Alkyd Varnish Clear, 256  
AMS-3170 Graphite Varnish Thinner, 1321  
Anti-Static Epoxy Polyamide Coating, 747  
AP-561 Type JM-3 Stripper, 1328  
Aquacom Waterbase Lacquer, 519  
Aquacom Waterbase Sanding Sealer, 517  
Aqua-Poly Waterborne 2-Part Polyurethane, 748  
Aqua-Poly Waterborne 2-Part Polyurethane Clear, 300  
Aqua-Star Series Waterbase Pool Paint, 749  
Aqueous Undercoater, 1260  
Aromatic Water-Borne Urethane Coating, 751

## **B**

B-60 Acrylic Solvent Base Coating, 562  
Baking Enamel Reducer, 1324  
Block Out Lacquer #37038 Flat Black, 654  
Boiled Linseed Oil, 1345  
Bucellatone, 1304  
Butoxy 33RC, 754

## **C**

C-1178-66 Type Catalyst, 616  
C-252-66 Type Catalyst, 619  
C740 Flat Black Primer, 1233  
C740 Water Reducible Lead-Free Alkyd Enamel, 694  
Ceramicoat, 31  
Ceramicoat Elastomeric Heat Shield Coating, 258, 756  
Chlorinated Polymer Traffic Paint, 407  
Chlorinated Rubber Metal Primer, 1047  
Chlorinated Rubber Primer, 946  
Corrosion-Guard Urethane Coating, 409

## **D**

D202 Rust Conversion Primer, 1121  
Damp Proof Slow-Dry Red Oxide Primer, 1037  
DC202 Rust Conversion Primer, 1075  
DC3 Surface Sealer, 758  
DC6571-805 High Heat Aluminum Coating, 759  
DC6571-805 Hi-Heat Aluminum Coating, 550  
DC701 Water Reducible Acrylic Enamel High Gloss, 680, 761  
DC701 Water Reducible Acrylic Gray Primer, 1210  
DC701 Water Reducible Acrylic Primer, 1212  
DC701 Water Reducible Acrylic Red Oxide Primer, 1214  
DC733 Epoxy Amine Coating #082 Munsell Blue, 615  
DC733 Epoxy Amine Coating NPC61661 FP5025 Type II, Class A, #17038 Gloss Black, 604  
DC733 Epoxy Polyamine Coating, 610, 622, 763  
DC733 Epoxy Polyamine Coating #011 White, 620  
DC733 Low VOC Epoxy Polyamine Coating, 628  
DC733 Low VOC Epoxy Pool Paint, 632, 765  
DC7337 Series Waterborne Acrylic Urethane Enamel, 334, 411, 536  
DC740 ADOT #1 Light Gray Primer, 1125  
DC740 ADOT #2 Off White Primer, 1250  
DC740 Agate Brown Oxide Primer, 1241  
DC740 Bunger Red Oxide Primer, 1243  
DC740 Bunger Red Primer, 1065  
DC740 Dipping Enamel Gray, 682  
DC740 Ferro Prime Gray, 1228  
DC740 Primer, 1235  
DC740 Ratmoore #1 Primer, 1218  
DC740 Ratmoore #4 Water Reducible White Primer, 1245  
DC740 Ratmoore #7 Water Reducible Gray Primer, 1220  
DC740 Ratmoore Primer, 1056, 1216, 1262  
DC740 Semigloss Convey Red Oxide Primer, 1239  
DC740 SSPC Ratmoore Primer, 1069  
DC740 Water Reducible #124042 Flat Black, 684  
DC740 Water Reducible Able White Primer, 1247  
DC740 Water Reducible Modified Enamel, 688  
DC740 Water Reducible Modified Enamel #450 Tan, 686  
DC740 Water Reducible Ratmoore TN Gray Primer, 1230  
DC740 Water Reducible Western Fab Gray Primer, 1225  
DC740 Water Reducible White Primer, 692  
DC740 Waterborne Wood Stain, 260, 767  
DC740 Western Fab Gray Industrial Primer, 1223

## **Index** (continued)

DC740ML Water Reducible Modified Enamel, 690  
Deer Valley Enamels, 579, 583  
Deer Valley Enamels Semigloss Matthews White, 585  
Deer Valley Gray Primer, 956  
Deer Valley Quick-Dry Aluminum, 575  
Diamond Rust Shield Red Primer, 1058  
DOD-24607 Non-Flaming Enamel, 670  
DOD-24607A Non-Flaming Enamel, 674  
DOD-P-15328C Pre-Treat Wash Primer, 1023  
DOD-P-21035A Zinc Compound, 1186  
Dual-Etch, 1300, 1338

### **E**

EB, 1329  
Eggshell Alkyd Enamel, 262  
Elastomeric Acrylic Tire Refurb Paint, 525  
Elastomeric Canvas Coating, 66  
Elastomeric Coating, 41, 58, 264  
Elastomeric Coating #4606, 47  
Elastomeric Coating Utility Elasto-Black, 17  
Elastomeric Epoxy Sealer, 1264  
Elastomeric Prime Coat Adhesive White, 64  
Elastomeric Primer, 39, 119  
Elastomeric Roof Coating, 43, 45  
Elastomeric White Primer, 319, 1135  
Elastopox Coating, 6  
Elastowall Coating, 52  
Electrostatic #7 Gray Primer, 976  
Electrostatic (611BC) Epoxy Primer, 769  
EMS52438 K0548 Type NPC61270-1 Graphite Varnish  
G8450, 554  
Enviro-Gard 100% Solids Epoxy Coating, 367  
Epoxy Crack Filler, 366, 597, 1339  
Epoxy Elastomeric Sealer, 413  
Epoxy Ester Alkyd Enamel Low VOC Hi-Solids, 772  
Epoxy Ester Primer, 978  
Epoxy Hi-Build Pool Paint, 785  
Epoxy Loop Sealant, 415, 774, 1348  
Epoxy Modified Polyurethane Coating, 298, 495  
Epoxy Polyamide Coating, 775  
Epoxy Polyamide Coating Fluorescent Finish, 777  
Epoxy Polyamide Coating Hi-Build, 779  
Epoxy Polyamide Hi-Build Topcoat, 625  
Epoxy Polyamide Red Oxide Primer, 1043  
Epoxy Polyamide Topcoat Hi-Build, 781  
Epoxy Polyamide Zinc Dust Primer, 1143  
Epoxy Polyamine Coating Metallic Series, 630  
Epoxy Polyamine Topcoat Hi-Build, 783  
Epoxy Pool Paint Primer White, 416  
Epoxy Pool Paint White Primer, 1266  
Epoxy Spot Sealer Clear, 608  
Epoxy White Primer, 1165  
Epoxy Zinc Rich Primer, 986  
Epoxy/Poly Hi-Build Anti-Graffiti, 770, 1346  
Exterior Graffiti Block-Out Paint, 153  
Exterior Wood Primer, 111

### **F**

Fast Dry Water-Reducible Primer, 992  
Ferro-Prime #36375 Steel Gray, 999  
Fire Resistant Paint White, 49  
Fire Resistant Sealer Clear, 187  
Fire Retardant Coating, 115  
Fire Retardant Primer Waterbase, 266  
Flat Alkyd Enamel, 543  
Flexi-Coat Rubberized Elastomeric Coating, 787  
Flexocryl Coating, 323  
Flexocryl Floor and Deck, 305, 328  
Floor and Deck Enamel, 364  
FP5025 Type I, Class C, 611BC Epoxy Amine Gloss Green  
Primer, 1148  
Franciscan Brown Primer, 1025

### **G**

G & G 305 Epoxy Coating, 789  
Galvanized Metal Primer, 1101  
Gila Coat Asphaltic Coating, 792  
Graffiti-Guard Polyurethane Clear, 487  
Gym Finish Varnish, 418

### **H**

HAPS Free Acrylic Gloss Clear, 555  
Hi-Build Acrylic Polyurethane, 485  
Hi-Build Epoxy Polyamide Primer, 1045, 1099, 1109  
Hi-Build Epoxy Polyamine Primer, 1268  
Hi-Build Latex Paint, 8  
Hi-Gloss Alkyd Enamel, 268  
Hi-Heat Coating, 552, 553  
Hi-Heat Coating #17038 Gloss Black, 539  
Hi-Heat Coating 1000 Degrees, 794  
Hi-Heat Coating 1200 Degrees, 795  
Hi-Heat Coating 800 Degrees, 793  
Hi-Heat Emissive Coating, 538  
Hinge Packs Touch-Up Kits, 803  
Hi-Solids Moisture-Cure Zinc Rich Primer, 980  
Hi-Solids Polyurethane, 420, 796  
Hi-Solids Polyurethane 2-1, 423  
Hi-Solids Polyurethane Fluorescent Finish, 799  
Hi-Solids Polyurethane Metallic Series, 801  
Hydro-Acrylic #3 Topcoat, 15  
Hydro-Acrylic ADOT #1, 15  
Hydro-Acrylic ADOT #1 Red Oxide Primer, 1071  
Hydro-Acrylic Coating, 25, 426  
Hydro-Acrylic Stain, 27  
Hydro-Acrylic Stain #30318, 303  
Hydro-Acrylic Stain Calle De Rio, 29  
Hydropox #1 Curb Red, 379  
Hydropox #1 DTM Acrylic Enamel High Gloss, 804  
Hydropox #1 Floor Coating, 428  
Hydropox #1 Marking Paint, 431  
Hydropox #1 Waterborne, 806  
Hydropox #1 Waterborne Primer, 1174



## Index (continued)

Hydropox #2 4-1 Epoxy, 433, 808  
Hydropox #2 4-1 Epoxy Masonry Coating, 438  
Hydropox #2 4-1 Epoxy Utility Coating, 445  
Hydropox #2 Epoxy Primer, 1171  
Hydropox #2 Flexocryl, 219, 270  
Hydropox #3B Waterborne, 810

### I

Industrial Alkyd Enamel Flat Clear, 595  
Industrial Alkyd Primer Western Fab Gray, 988  
Industrial Dipping Enamel, 545  
Industrial Machinery Enamel Semigloss, 587, 593  
Industrial Oilbase White Primer, 1079  
Injection Epoxy Filler, 450  
Inorganic Zinc Rich Reducer, 1319  
Interior Acrylic Enamel Eggshell Finish, 9  
Interior Latex Flat, 11  
Interior Latex Semigloss, 13  
Isopropyl Alcohol, 1303

### J

Jet-Dri Gray Primer, 962  
JM-3 Stripper, 1330, 1349

### L

Lacquer Sanding Sealer, 227, 696  
Lacquer Topcoat, 228, 697, 699  
Latex Blended Acrylic, 81, 83, 85, 87  
Latex Blockout White, 1103  
Latex Dry Fall Coating, 51  
Latex Flat, 60, 67, 73, 79, 165, 169  
Latex Flat Exterior, 157  
Latex Sego-Acrylic Primer, 1270  
Latex Semigloss Enamel, 129, 139, 141  
Latex Semigloss Enamel Exterior, 143  
Latex Semigloss Exterior, 131  
Latex Semigloss Interior, 133  
Latex White Primer, 1272  
Litoxy Sealer, 812, 1350  
Log Oil Wood Sealer Clear, 193  
Long Oil Alkyd Flat, 207  
Low VOC Epoxy Polyamine Coating, 1176  
Low VOC Fab Gray Industrial Primer, 1005  
Low VOC Lead Free Epoxy Polyamine Primer, 1178  
Low VOC Quick Dry Enamel, 813  
Low VOC Quick-Dry Enamel, 573, 577  
Low VOC Quick-Dry Enamel Close Blue, 581  
Low VOC Universal Phenolic-Alkyd Metal Primer, 1049

### M

M. W. Alkyd Red Oxide Primer, 1073  
Maincote Acrylic Enamel, 534  
Masonry Acrylic Coating Flat Clear, 350

MCS6074D Aerosol Enamel Black, 815  
Metal Pretreatment Wash Primer, 1015  
Metal Weld Ratmoore Red Oxide Primer, 1067  
Metallic Series Acrylic Coating, 816  
Metallic Series Industrial Alkyd Enamel, 818  
Methacrylate Acrylic Lacquer Clear, 452  
MIL-A-6091 Denatured Alcohol, 1322  
MIL-C-17504C Acrylic Coating Clear, 661  
MIL-C-22750D Type I and II, Epoxy Polyamide Coating, 820  
MIL-C-22750F Epoxy Hi-Solids Coating, 821  
MIL-C-22750F Type I and II, Epoxy Polyamide Coating, 612  
MIL-C-450C Bituminous Coating, 651, 653, 822  
MIL-C-46168D Polyurethane, 823  
MIL-C-46168D Type IV, 825  
MIL-C-81773C Polyurethane, 479, 827  
MIL-C-83286 Polyurethane RAL-6021 Green, 493  
MIL-C-83286B Catalyst, 497  
MIL-C-83286B Polyurethane, 829  
MIL-C-83286B Polyurethane Coating, 483  
MIL-C-85285B(AS) 4-1 Polyurethane Catalyst, 499  
MIL-C-85285C Polyurethane, 831  
MIL-DTL-15090D Formula 111 Equipment Enamel Light Gray, 833  
MIL-DTL-24441/20 #150 Green Primer, 1160  
MIL-DTL-24441/21A #151 Haze Gray, 598  
MIL-DTL-24441/22A #152 White, 627  
MIL-DTL-24441/23A Black Topcoat, 605  
MIL-DTL-24631 Type II, 648  
MIL-DTL-24631/1C Black Epoxy Coating, 650  
MIL-E-11195E Fast Dry Enamel, 834  
MIL-E-15090C Formula 111 Equipment Enamel, 836  
MIL-E-16663A Enamel Semigloss, 634  
MIL-E-22118B Electrical-Insulating Enamel, 671  
MIL-E-24635B Silicone Alkyd Enamel, 640  
MIL-E-52891B(ME), 838  
MIL-E-5558A Type I, Wrinkle Finish Paint, 840  
MIL-E-7729B Alkyd Enamel Gloss, 842  
MIL-L-10287B Cellulose Nitrate Lacquer, 844  
MIL-L-19537C Acrylic Nitro Cellulose Lacquer Gloss, 845  
MIL-L-19537C Acrylic Nitro-Cellulose Lacquer Gloss, 675  
MIL-L-19538C Acrylic Nitro-Cellulose Lacquer Camouflage, 847  
MIL-L-46159A Low Reflective Acrylic Lacquer, 849  
MIL-L-52043C Lacquer Semigloss, 851  
MIL-L-81352A Acrylic Lacquer, 853  
MIL-L-81352B Type I, Acrylic Lacquer, 855  
MIL-L-81352B Type III, Polyurethane, 857  
MIL-P-11414E Red Oxide Primer, 1202  
MIL-P-14105D Heat Resisting Coating, 859  
MIL-P-15930C Comp. G, Vinyl Zinc Chromate Primer, 1195  
MIL-P-21035B Zinc Dust, 1184, 1189  
MIL-P-21563B Fluorescent Paint, 662  
MIL-P-21600A Fluorescent Paint, 861  
MIL-P-22332B Comp. G, Zinc Chromate Primer, 1204

## Index (continued)

MIL-P-22332B Zinc Chromate Primer, 1206  
MIL-P-23377F Type I and II, Epoxy Polyamide Coating, 862  
MIL-P-23377F Type I and II, Epoxy Polyamide Primer, 1274  
MIL-P-23377G Class C, Epoxy Polyamide Primer, 1275  
MIL-P-23377G Class N, Non-Chromate Formulation Epoxy Polyamide Primer, 1019  
MIL-P-24380B(SH), 645  
MIL-P-24441/20(SH) #150 Green Primer, 1156  
MIL-P-24441A(SH) #150 Green Primer, 1157  
MIL-P-26915B Class B, Zinc Dust Primer, 1276  
MIL-P-26915B Type I, Class B, Zinc Dust Primer, 1180  
MIL-P-26915B Type I, Zinc Dust Primer, 1182  
MIL-P-28577B Waterborne Acrylic Red Oxide Primer, 1198  
MIL-P-38336 Inorganic Zinc Rich Primer, 974  
MIL-P-46105 Zinc Rich Primer, 1278  
MIL-P-52108A Stencil/Obliterating Paint, 665  
MIL-P-52192B Epoxy Primer, 863  
MIL-P-53022B Epoxy Polyamide Primer, 864  
MIL-P-53022B Epoxy Primer, 1280  
MIL-P-53022B Type I, Epoxy #26622 Gray Primer, 1188  
MIL-P-53022B Type II, Epoxy #26622 Gray Primer, 1191  
MIL-P-53030 Primer, 1161, 1163, 1169  
MIL-P-53030A Water Reducible Epoxy Primer, 1145, 1281  
MIL-P-85582C Waterborne Epoxy Primer, 1153  
MIL-P-8585A Zinc Chromate Primer, 1196  
MIL-PRF-22750F Hi-Solids Low VOC Epoxy Coating, 865  
MIL-PRF-23377G Class C, Epoxy Polyamide Primer, 1283  
MIL-PRF-23377G Class N, Epoxy Polyamide Primer, 1115  
MIL-PRF-23377H Class C, Epoxy Polyamide Primer, 1119  
MIL-PRF-23377H Class N, Non-Chromate Formulation Epoxy Polyamide Primer, 1022  
MIL-PRF-23377H Type I, Class C, Epoxy Polyamide Primer, 1118  
MIL-PRF-24635B Silicone Alkyd Enamel, 643  
MIL-PRF-24635C Type II, Class 2, Silicone Alkyd Enamel, 678, 866  
MIL-PRF-26915D Type I, Class A, Zinc Dust Primer, 1284  
MIL-PRF-26915D Type I, Zinc Dust Primer, 1192  
MIL-PRF-3043C Permanent Resin Coating, 868  
MIL-PRF-81352B Type I, Acrylic Lacquer, 869  
MIL-PRF-81352B Type III, Polyurethane, 871  
MIL-PRF-85285C Polyurethane, 503, 873  
MIL-PRF-85285C Polyurethane Coating, 481  
MIL-PRF-85285D Class H, 875  
MIL-PRF-85285D Type I, Class H, 877  
MIL-PRF-85582C Waterborne Epoxy Primer, 1158  
MIL-PRF-85582D Waterborne Epoxy Primer, 1286  
MIL-R-3043B Permanent Resin Coating, 669  
MIL-T-19544E Acrylic Thinner, 1311  
MIL-T-6095B, 1331  
MIL-T-81772B Type I, Polyurethane Thinner, 1306  
MIL-T-81772B Type II, Epoxy Thinner, 1310  
MIL-T-81772B Type III, Polyurethane Thinner, 1318

MIL-V-12276D Type II, Phenolic Baking Varnish, 660  
MIL-V-16399A Type B, Moisture Proof Varnish, 659  
MIL-V-173C, 879  
MIL-W-5044C Nonslip Walkway Compound, 880  
Mineral Spirits, 1312  
Moisture Cure Polyurethane, 489  
Moisture-Cure Zinc Rich Primer, 972  
MPI #28 Marine Spar Varnish Exterior Gloss Clear, 221  
MPI #32 Traffic Paint, 454  
Multi-Purpose Primer, 948, 1089  
M-Y-R-A Adhesive Epoxy, 456, 881, 1351

## N

Nitrocellulose Lacquer, 883  
Non-Skid Coating, 272, 457  
Non-Skid Epoxy Coating, 613  
Non-Skid Floor Coating Roughcoat, 459  
Non-Skid Oilbase Coating, 461  
NPC61612-2 612A Epoxy Amine #34151 Green Primer, 1151  
NPC61646 Wipecoat #6 Epoxy Amine Green, 1152

## O

Oilbase Wood Stain Exterior, 179  
Oilbase Wood Stain Interior, 181

## P

P-415A-66 Epoxy Gray Primer, 1141  
P-415A-66 FP5025 Type I, Class A, E, C, MCS9010 Epoxy #34151 Green Primer, 1288  
P-415A-66 W/C-415A-66 Converter Epoxy #34151 Green Primer, 1252  
P-674-66 Gray Primer, 958  
PCS5401 Type I, Class A, Epoxy Amine Primer, 1173  
Pigmented Concrete and Wood Sealer Semi-Transparent Brown, 301  
Polypane Polyurethane, 885  
Polyrock CF Crack Filler, 377  
Polyurethane Alkyd Enamel, 569  
Polyurethane Alkyd Enamel Semigloss, 213  
Polyurethane Coating, 505  
Polyurethane Gloss Interior/Exterior, 191  
Polyurethane Satin Varnish, 189  
Polyurethane Varnish Clear, 274  
Pool Paint Thinner, 1316  
Portland Cement Primer, 1091  
Protector Silicone Sealer Clear, 201

## Q

Quick Dry Exclusive Gray Primer, 982  
Quick Dry Therma Gray Primer, 1003  
Quick-Dry Baking Enamel, 556  
Quick-Dry Epoxy Primer, 1167

## Index (continued)

### R

Ratmoore #2AS Red, 1039  
Ratmoore #4 White Primer, 1097  
Ratmoore #5 Gray Primer, 994  
Ratmoore 200LCF Series Primer, 1289  
Ratmoore Maricopa Red Primer, 1060  
Ratmoore Primer, 950, 1054, 1085  
Ratmoore Primer 1990 Revision, 952  
Renoozit DC7337 Urethane Acrylic Coating, 887  
Rock Lock Clear, 310  
Rubber Base Sealer, 276  
Rust-Gard Red Oxide Primer, 1063

### S

Sealer White Primer, 1081  
Semigloss Alkyd Enamel, 183  
Semigloss Enamel, 563  
Sharon Ratmoore White Primer, 1095  
Shop Coat Red Oxide Primer, 1031  
Silicone Alkyd Enamel Hi-Heat, 565  
Silicone Alkyd Enamel Tempe Bronze, 559  
Simulated Metallic Series Waterbase Acrylic Coating, 889  
Spar Varnish Alkyd Resin, 185  
Spar Varnish Gloss Clear, 195  
Spar Varnish Phenolic Resin, 197  
Special Shop Coat Red Oxide Primer, 1052  
SSPC-11 Red Oxide Primer, 1029  
SSPC-20 Type IC, Inorganic Zinc Rich Primer, 984  
SSPC-Paint 25 Red Oxide Primer, 1041  
Standard Set Epoxy Adhesive, 617  
Sunguard Elastomeric Roof Coating, 71  
Superflex Floor and Deck, 338  
Synthetic Reducer, 1308

### T

T-120-66 Wash Primer Thinner, 1307  
T-262A-66 Epoxy Thinner, 1313  
T-77 Butoxy Thinner, 1301  
Tar Guard Additive, 561  
Tennis Court Coating, 315  
Toluidine Red Tint #0725, 540  
TPD-24607 Non-Flaming Enamel, 668  
Tree Trunk Paint, 155  
Triad Special Red Oxide Primer, 1077  
TT-C-542E Moisture Cure Polyurethane Clear, 491  
TT-C-542E Moisture Cure Urethane Clear, 657  
TT-E-001384 Acrylic Enamel, 891  
TT-E-1593B Silicone Alkyd Enamel, 912  
TT-E-485F, 893  
TT-E-485F Comp. G, 663  
TT-E-487E Floor and Deck Enamel, 463  
TT-E-489G Class A, Alkyd Enamel Gloss, 894  
TT-E-489H Alkyd Enamel Gloss, 896  
TT-E-489J Alkyd Enamel Gloss, 898  
TT-E-490E Silicone Alkyd Enamel, 900

TT-E-508C Alkyd Enamel Semigloss, 278  
TT-E-509C Type I, Class 1, Alkyd Enamel Odorless Semigloss, 280  
TT-E-515A Quick Dry Enamel, 902  
TT-E-516A Quick Dry Enamel, 904  
TT-E-527C Lusterless Alkyd Enamel, 906  
TT-E-527D Lusterless Alkyd Enamel, 907  
TT-E-529 Alkyd Enamel Semigloss, 908  
TT-E-529G Alkyd Enamel Semigloss, 910  
TT-E-529G Type II, Alkyd Baking Enamel, 646  
TT-E-751C Ethyl Acetate, 1332  
TT-L-20A Lusterless Lacquer, 914  
TT-L-32A Cobblestone Semigloss, 666  
TT-L-32A Lacquer Gloss, 672, 916  
TT-L-50E Type I, Lacquer, 918  
TT-L-50G Type II, Lacquer, 919  
TT-L-58E Lacquer Gloss, 637  
TT-M-261 Methyl Ethyl Ketone, 1305  
TT-N-95B Aliphatic Naphtha, 1320  
TT-N-97C Type II, Aromatic Naphtha, 1325  
TT-P-102E Alkyd Enamel, 287  
TT-P-102F Long Oil Alkyd Enamel, 923  
TT-P-110C Type I, Traffic Paint Black, 340  
TT-P-115F Type I, Traffic Paint, 360  
TT-P-115F Type II, AMD. 2, Traffic Paint, 384  
TT-P-115F Type II, Traffic Paint, 358  
TT-P-1411A Cementitious Paint, 677  
TT-P-1511B Latex Semigloss Enamel, 135  
TT-P-1757A Zinc Chromate Primer, 1208, 1291  
TT-P-1757A/P-759A-66 Zinc Chromate Primer, 1017  
TT-P-1757B Type I, Class C, Aerosol Zinc Chromate Primer, 941  
TT-P-1757B Type I, Class C, Zinc Chromate Primer, 1293  
TT-P-1757B Type I, Class N, Non-Chromate Primer, 1116  
TT-P-1757B Type II, Class C, Zinc Chromate Primer, 1020  
TT-P-1952B Waterbase Traffic Coating, 471  
TT-P-1952C Waterbase Traffic Coating, 473  
TT-P-1952D Waterbase Traffic Coating, 475  
TT-P-19D Acrylic Latex, 281  
TT-P-26C Fire Retardant, 283  
TT-P-26C Fire-Retardant Coating, 649  
TT-P-2756A Polyurethane Coating, 925  
TT-P-28G Hi-Heat Coating, 547  
TT-P-320D Aluminum Pigment, 924  
TT-P-38E Aluminum, 635  
TT-P-54C Acid Resistant Lacquer, 920  
TT-P-636 Type Vulcraft Gray Primer, 970  
TT-P-636D Red Oxide Primer, 1033  
TT-P-641G Type III, Zinc Primer, 960  
TT-P-645A Zinc Chromate Primer, 1027  
TT-P-664D Red Oxide Primer, 1035  
TT-P-81E Alkyd Enamel, 285  
TT-P-85E Traffic Paint, 465  
TT-P-87D Traffic Paint, 467  
TT-P-91D Rubberized Deck Enamel, 469  
TT-P-95C Chlorinated Rubber Coating, 567, 921  
TT-S-171C Class 2, 926  
TT-S-178B Floor Coating, 477

## **Index** (continued)

TT-S-223B Waterbase Acrylic Sealer, 382  
TT-S-708A Oilbase Wood Stain Exterior, 289  
TT-S-711C Oilbase Wood Stain Interior, 291  
TT-T-266D Dope and Lacquer Thinner, 1309  
TT-T-291F Mineral Spirits, 1315  
TT-T-306C Synthetic Resin Thinner, 1333  
TT-T-306C Type I, Synthetic Resin Thinner, 1314  
TT-T-306E Synthetic Resin Thinner, 1334  
TT-T-548D Toluene, 1302, 1326  
TT-V-109C Phenolic Spar Varnish, 656  
TT-V-119D Phenolic Spar Varnish, 222  
TT-V-71H Acrylic Coating Exterior, 354  
TT-W-00572 Type Sealer, 927, 1352  
TT-X-916 Xylene, 1317

### **U**

Ucrl #3770 Urethane Acrylic Coating, 929  
Ucrl #3770 Urethane Acrylic Coating Clear Gloss, 931  
Urethane 3-1 Coating, 500  
Urethane Acrylic Coating Ucrl #3770 Gloss Clear, 509  
U-V Res III Acrylic Epoxy, 933  
U-V Res III Epoxy Satin Finish, 935

### **V**

Varnish Fire Resistant Clear, 203, 205  
Varnish Gloss Clear Interior, 199  
Vinyl Acrylic Ceiling Paint, 159  
Vinyl Acrylic Latex Flat, 163, 293

Vinyl Acrylic Primer, 954  
Vinyl Enamel System, 571  
Vinyl Floor Enamel, 362

### **W**

Waterbase Acrylic Coating, 54, 321  
Waterbase Acrylic Enamel ADOT Pole Brown, 523  
Waterbase Acrylic Pool Deck Coating, 332  
Waterbase Acrylic Sealer, 21, 308, 311, 313, 1295  
Waterbase Aluminum Coating, 526  
Waterbase Anti-Graffiti Epoxy Coating Clear, 606  
Waterbase Concrete Stain, 336  
Waterbase Enamel, 295  
Waterbase Flat Black, 515, 528  
Waterbase Polyurethane Enamel, 532  
Waterbase Pool Paint, 1354  
Waterbase Silicone Clear Sealer, 1297  
Waterbase Traffic Paint, 317  
Waterbase Wood Stain, 173  
Waterborne 2-Part Aqueous Polyurethane, 386  
Waterborne Acrylic Enamel, 330  
Waterborne Hydro-Acrylic AG Red Oxide Primer, 1133  
Wood Primer Exterior, 1137

### **Z**

Zinc Chromate Flat Black Primer, 1009  
Zinc Phosphate Alkyd Primer, 1111  
Zynolyte Speed Enamel, 939