



# TECHNICAL DATA SHEET

TECHNICAL DATA SHEET  
100% ACRYLIC LATEX FLAT  
301 SERIES  
PAGE 1 OF 2

**PRODUCT:** An interior/exterior grade 100% acrylic flat paint.

**DESCRIPTION:** A 100% acrylic flat coating that will provide excellent durability and weather resistance. Intrepid's 100% acrylic flat paint is formulated for interior/exterior use. This product produces a film that has excellent adhesion, chalk and fade resistance.

**PROPERTIES:** COLOR..... Full Range  
GLOSS..... <10 Gloss Units  
SOLIDS(Weight)..... 66 - 69%  
THEORETICAL COVERAGE..... 350-400 sq.ft./gal  
**DRYING TIME-AT 75 DEGREES F:**  
TO TOUCH..... Within 15 Minutes  
TO RECOAT..... 2 - 4 Hours  
VEHICLE TYPE..... Acrylic

**ADVANTAGES:** (1). Early Water Resistance.  
(2). Resistant to Mildew.  
(3). Water-Base.  
(4). Abrasion Resistant.  
(5). Superior Exterior Durability.

**USES:** (1). Exterior Walls.  
(2). Exterior Stucco & Masonry.  
(3). Exterior Metal Surfaces.  
(4). Exterior Block.  
(5). Exterior Wood Surfaces.



# TECHNICAL DATA SHEET

TECHNICAL DATA SHEET  
ACRYLIC LATEX FLAT  
301 SERIES  
PAGE 2 OF 2

**APPLICATION & REDUCTION:**

Intrepid's 100% Acrylic Latex Flat may be thinned with water if necessary. Use at packaged consistency for most applications. May be applied by brush, roll or spray.

**SURFACE PREPARATION:** Surface must be clean and free of grease, oil, chalk, dust, and other contaminants. Loose or peeling paint must be removed by sanding, scraping, waterblast or sandblasting. All mildew must be removed before application. Remove by scrubbing with a solution made of 1 quart household bleach in 3 quarts of water. DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER MIXTURE. Scrub to remove any contaminants. Careful surface preparation is the key to a long lasting and successful job.

**PRECAUTIONS:**

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.

KEEP FROM FREEZING!