



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
ACRYLIC LATEX
PRIMER SEALER
PAGE 1 OF 2

PRODUCT: An acrylic latex primer / sealer.

DESCRIPTION: A waterborne acrylic water reducible primer. It offers excellent early water resistance and a sound base for use as a waterbase primer for masonry, maintenance, drywall, and OEM finishes.

PROPERTIES: COLOR..... WHITE
SOLIDS (Weight)..... 66 - 69%
THEORETICAL COVERAGE..... 575 sq.ft./gal
DRYING TIME-AT 75 DEGREES F:
TO TOUCH..... Within 15 Minutes
TO RECOAT..... 2 - 4 Hours
VEHICLE TYPE..... Acrylic

ADVANTAGES: (1). Tough and Durable.
(2). Quick Drying.
(3). Water-Base.
(4). Cleans Easily.
(5). High Hiding.

USES: (1). Interior/Exterior
(2). Doors
(3). Wallboard
(4). Masonry
(5). Metal
(6). Trim



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
ACRYLIC LATEX
PRIMER SEALER
PAGE 2 OF 2

APPLICATION & REDUCTION:

Intrepid's Acrylic Latex Primer may be thinned with water if necessary. Use at packaged consistency for most applications. May be applied by brush, roll or spray.

SURFACE PREPARATION: Surface must be clean and free of grease, oil, chalk, dust, and other contaminants. Loose or peeling paint must be removed by sanding, scraping, waterblast or sandblasting. All mildew must be removed before application. Remove by scrubbing with a solution made of 1 quart household bleach in 3 quarts of water. DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER MIXTURE. Scrub to remove any contaminants. Careful surface preparation is the key to a long lasting and successful job.

PRECAUTIONS:

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.

KEEP FROM FREEZING!