



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
IMPERTHON-38
CLEAR GLOSS VARNISH
PAGE 1 of 2

PRODUCT: An air/bake dry, moisture resistant clear gloss modified alkyd varnish that protects and insulates. This coating is highly penetrating and impenetrable once applied.

DESCRIPTION: This coating is a moisture and fungus resistant varnish for the treatment of communications, electronic and related equipment. It may also be used on tools and materials that are to be transported by ship. It dries to a smooth, hard film that resists cracking and splintering.

PROPERTIES: COLOR..... Clear
FINISH..... Gloss
SOLIDS (Weight)..... 51 - 54%

DRYING TIMES (AMBIENT TEMP):

SET-TO-TOUCH..... Within 60 Minutes
DRY TACK FREE..... Within 5 Hours

DRYING TIMES (BAKE SCHEDULE):

SET-TO-TOUCH..... 30 Minutes
BAKE TIME..... 30 Minutes (350° Fahrenheit)

ADVANTAGES: (1). Fast Dry
(2). Moisture Resistant
(3). Fungus Resistant
(4). Air Dry / Bake Dry (For Quicker Turn Around)

USES: (1). Electronic Equipment
(2). Communications Equipment
(3). Electrical Equipment
(4). Tools
(5). Electric Parts/Wires



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
IMPERTHON-38
CLEAR GLOSS VARNISH
PAGE 2 of 2

APPLICATION: Surface must be clean, dry and properly prepared before application. Coating may be applied by dip, brush, roll or spray.

Air dry for 5 hours (dry hard) - 7 days full cure.

Bake for 30 minutes at 350° Fahrenheit after a 30 minute air dry to force cure the coating

PRECAUTIONS:

CONTENTS ARE FLAMMABLE.
USE WITH ADEQUATE VENTILATION.
KEEP FROM HEAT, SPARKS AND FLAME.
READ MSDS BEFORE USE.

SHELF LIFE: 1 YEAR FROM DATE OF MANUFACTURE
** READ MSDS BEFORE USE **