



TECHNICAL DATA SHEET

**TECHNICAL DATA SHEET
WALKWAY COMPOUND-NONSLIP
MIL-PRF-24667C**

PRODUCT: A high durability deck coating for the exterior of aircraft and naval surfaces.

DESCRIPTION: MIL-PRF-24667C WALKWAY COATING is a deck coating for the exterior of aircraft and naval surfaces.

PROPERTIES:

COLORS..... Per Fed.Std. 595C
FINISH..... Various
SOLIDS (Weight)..... >90%
DRYING TIMES:
FULL HARDNESS..... 48 Hours

ADVANTAGES:

- (1). Non-Slip.
- (2). Air Dry.
- (3). Brushable.
- (4). Durable.
- (5). Fast Dry.

USES:

- (1). Exterior Aircraft / naval decks.
- (2). Heavy Traffic Areas.
- (3). Non-Slip Requirements.

APPLICATION:

MIL-PRF-24667C can be rolled, squeegeed and brushed with proper tools. Mix part A with part B in a 4:1 mix ratio. It is very important to mix both parts well before use. Also very important is the thorough mixing after combining part A with part B. For longer pot life we suggest that after mixing well, admixed material be spread immediately to substrate. The thinner the mil of the material, the longer the pot life will be. This material has an in-the-pot pot life of about 4 hours depending on temperature, etc.