



# TECHNICAL DATA SHEET

TECHNICAL DATA SHEET  
MIL-PRF-680C  
(AMS 2641)

## PRODUCT DESCRIPTION:

Dry cleaning and degreasing solvent consisting of three types of petroleum distillates: Ty. I - "Stoddard Solvents", Ty. II - 140° Fahrenheit Solvent, and Ty. III - 200° Fahrenheit Solvent (unavailable through TriCom Coatings, Inc.) They are used for dry cleaning, spot and stain removing, and for degreasing of machine parts in equipment maintenance. Meets the requirements of AMS2641 specification as well.

## TYPICAL PROPERTIES:

- (1). **FLASH POINT**  
Ty. I - 100° Fahrenheit  
Ty. II - 140° Fahrenheit  
Ty. III - Not Available through Intrepid Coatings, Inc.
- (2). **INITIAL BOILING POINT**  
Ty. I - 149° Fahrenheit  
Ty. II - 177° Fahrenheit  
Ty. III - Not Available through Intrepid Coatings, Inc.
- (3). **WEIGHT PER GALLON**..... 6.44 - 6.6 Lbs
- (4). **PERCENT VOLATILES**..... 100%

## PRECAUTIONS:

USE WITH ADEQUATE VENTILATION.  
AVOID CONTACT WITH SKIN AND EYES.  
READ MATERIAL SAFETY DATA SHEET BEFORE USING.  
KEEP OUT OF THE REACH OF CHILDREN.  
FOR INDUSTRIAL USE ONLY.  
CONTENTS ARE FLAMMABLE.