



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
TT-V-51
VARNISH ASPHALT
PAGE 1 OF 2

PRODUCT: A ready to use, low VOC asphalt varnish for interior or exterior applications. Provides an elastic weatherproof film that effectively seals out air and moisture for a variety of metal substrates including marginally prepared rusted surfaces and wood.

PROPERTIES: COLOR..... #17038 Gloss
Black SOLIDS BY WEIGHT..... 54 - 55%
VISCOSITY #4 Ford Cup.....46 - 60 Seconds
VOLATILE ORGANIC COMPOUNDS (VOC)....366 Grams/Liter

DRYING TIMES:

SET TO TOUCH: WITHIN 3 HOURS
DRY HARD: WITHIN 24 HOURS

USES:

- (1). Weather Proofing for Metal
- (2). Sealing of Metal Surfaces
- (3). Corrosion Protection of Metal and wood



TECHNICAL DATA SHEET

TECHNICAL DATA SHEET
TT-V-51
VARNISH ASPHALT
PAGE 2 OF 2

APPLICATION & REDUCTION:

Mix well. Apply by roller, brush or spray. Thin and cleanup equipment with MIL-T-81772B Type III Reducer or Xylene.

SURFACE PREPARATION:

Surface must be clean, dry and free of all contamination before application. Substrate must be clean and free of all oil, grease and foreign material. Badly rusted or pitted steel should be cleaned of loose rust by commercial sandblasting or wire brushing. Aluminum or galvanized non-ferrous metals should be acid etched or primed with a metal pretreatment wash primer such as MIL-C-8514C.

PRECAUTIONS:

Contents are FLAMMABLE.

Keep away from heat and open flame.

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.