



TECHNICAL DATA SHEET

**TECHNICAL DATA SHEET
V92VC10
PHENOLIC VARNISH SEALER**

PRODUCT: An air dry, moisture and fungus resistant clear gloss varnish. Protects and insulates.

DESCRIPTION: V92VC10 coating is a moisture and fungus resistant varnish for the protection of metals. May also be used on tools and materials that are to be transported by ship. Dries to a smooth, hard film that resists cracking and splintering.

PROPERTIES: COLOR..... Clear
FINISH..... Gloss
SOLIDS (Weight)..... 51 - 54%

DRYING TIMES:
SET-TO-TOUCH..... Within 60 Minutes DRY
TACK FREE..... Within 5 Hours

ADVANTAGES: (1). Fast Dry
(2). Moisture Resistant
(3). Fungus Resistant
(4). Air Dry

USES: (1). Electronic Equipment
(2). Communications Equipment
(3). Electrical Equipment
(4). Tools / Metal Parts
(5). Electric Parts/Wires

APPLICATION: Surface must be clean, dry and properly prepared before application. May be applied by brush, roll, dip, or spray.
AEROSOL CANS: Vigorously shake can for one minute to to thoroughly mix coating. Shake can occasionally while spraying. Hold can approximately 12" from surface to be painted.

SHELF LIFE: 1 YEAR FROM DATE OF MANUFACTURE **
READ MSDS BEFORE USE **